



TOUCH MONITOR



MONITOR



OPEN FRAME



TOUCH SCREEN



DIGITAL SIGNAGE



TOUCH TABLE



FLOOR STANDING



VIDEOWALL

www.worldtradedisplay.com

MONITOR

Monitor Solutions - LAY Wallmount Series



Display & Digital Signage Solutions

Wide Range, Easy & Accurate

Make your choice from various interactive display, videowall & digital signage discovering the multi-touch technology.

All in One Solutions

WTD solutions available also with Android/PC included, to satisfy the space & performances requests in only one item.

Common Scenarios

Innovative & communicative creativity, conceived & designed to meet different needs in the outdoor/indoor environments.

Benefits

Wide range of dimensions designed to cover all the most common usage scenarios in the professional markets, where it's also required high brightness or protection against high temperatures, thanks to our wide range of products such as videowall, open frame, touch display & digital signage solutions.

FEATURES	REMARKS	SPECIFICATIONS
Display	Type of product	Monitor
	Panel Size available	65"
	Active Area	65" 1426 x 801 mm 16:9 1920 x 1080
	Aspect Ratio	
	Resolution	
	Brightness	500 cd/m2
	Colors	16,7 million
	Viewing Angle	Horizontal (left/right): 178° Vertical (up/down): 178°
	Response Time (Pixel)	6,5/ 6 ms (Range)
	Contrast Ratio	4000:1
	Input Video Format	RGB Analog/ DVI-D /HDMI
	Input Video Signal	VGA/ HDMI
	Input Frequency	Horizontal: 30 - 82 kHz Vertical: 60 - 75 Hz
	High 4K Resolution	On Demand
	High Brightness	On Demand
Double Display	No	
PC Functions	CPU	-
	RAM	-
	SSD	-
	Connections	-
	Media Player	-
	System OS	-
	Android	-
	OPS Module Slot	No
Other Function	-	
Touch Functions	Technology	PCAP
	Point	10
	Interface	USB
	Surface Hardness	≥7 H
	Resolution	4096x4096
	Response Time	<12/ <10 ms
	Input Method	Finger or Capacitive Pen
Connectivity	Interface	USB
	Speaker	5W x 2
Function Conditions	Relative Humidity	Operating: 20% ~ 80% Storage: 10% ~ 90%
	Temperature Range	Operating: 0° ~ 50°C Storage: -20° ~ 70°C
	Screen Position	Landscape (Default) or Portrait
Mechanical	Installation (VESA)	200x200/ 400x400 Stand Mount
	Sheet Material	Alluminium frame, tempered glass face & cold-rolled sheet body
	Glass	Tempered Glass
	Enclosure Color	Black and Alluminium Gray Border
Power & Accessory	Power Supply	AC 100-240V Input DC 12V, 24V 50/60 Hz
	Power Cons. (Max)	70W/ 95W (Range)
	Cables	Power Supply with Cable Schuko

FEATURES	REMARKS	SPECIFICATIONS
	Input Connector	AC: Cable Power Schuko
Packaging	Dimension (Net) (L x W x H) Weight (Single)	65" 1500 x 69 x 875 mm 44 Kg
	Carton Dimension (L x W x H)	On Demand
Policy	Warranty	2 Years (Panel 1 Year)
	Agency Approval	CE - FCC - CCC
Other/ Upgrade	Extra Time Warranty	Please contact us if you need more informations
	Different Version	Available also with High Brightness and other kind od panel
		Special mechanical design
	Notes	Panel specification above comes from typical panel and for reference only, please contact our sales for the final confirmation, if needed.