

worldtradedisplay.com



OUTDOOR KIOSK DIGITAL SIGNAGE

Floor Standing Touch Screen NANOLITH Series No Touch/ Player/ Android/ PC







Your choice to discover the technologies



Wide range of innovative digital products



Increase your growth and company profit



OUTDOOR KIOSK DIGITAL SIGNAGE

NANOLITH Slim Series No Touch/ Player/ Android/ PC

Panel Specification	Display Size (inch)	43	55	65	75	
	Display Ratio	16:9	16:9	16:9	16:9	
	Active Area (H x V) (mm)	941 x 530	1210 x 680	1428 x 803	1650 x 928	
	Viewing Angle (H/ V)	178/178	178/178	178/178	178/178	
	Brightness (cd/m2)	3000 nits	3000 nits	3000 nits	3000 nits	
	Contrast Ratio	1000:1	1000:1	1000:1	1000:1	
	Display Resolution	1920 x 1080	1920 x 1080	1920 x 1080	1920 x 1080	
			I		/	
Touch Sensor O Touch Optional)	Type/ Points	PCAP 10P	PCAP 10P	PCAP 10P	PCAP 10P	
	Size	43	55	65	75	
	Active Area (mm)	941 x 530	1210 x 680	1428 x 803	1650 x 928	
	Total Thickness	6 mm	6 mm	6 mm	6 mm	
	Version	Outdoor				
	Special Treatment	Tempered (AR Anti-Reflective/ AG Antiglare/ Bonding)				
	Interface Type	USB				
	Compatible O/S	Windows, Linux, Others				
Monitor Specification	Installation (VESA)	4	-		-	
	Version/ Style	Outdoor				
	Interface	- /				
	Input Voltage		AC 100-240 V ~ (+,	/- 10%) 50/60 Hrz		
	Power Consumption Max(W/h)	400	550	650	750	
	Media Player	Yes				
	Speaker	2x5W Built in Stereo				
	Warrantly	2 Years (1 year fot the panel)				
	Certifications	CE - FCC - ROHS - Others on Demand				
PC System (Optional)	CPU	i3/ i5/ i7				
	RAM	4/ 8/ 16 Gb				
	SSD	64/ 128/ 256 Gb				
	Network	Wi-Fi, RJ45, VGA, HDMI 1.4, HDMI 2.0, 4xUSB 3.0				
	System O.S.	Windows 10 Trial				
	Other Function					
Android (Optional)	O.S. Version	Android 9.0 or higher version				
	Processor	T972 (1.9GHz octa core)				
	Media Formats	Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG)				
	Media Resolutions	1920 x 1080				
	RAM	2 Gb				
	Flash	16 Gb EMMC				
	USB	USB 2.0				
	LAN	10M/100M Ethernet				
	Wi-Fi	802.11 b/g/n Wi-Fi				
	1 *****					
	Temperature (Consumer)		Consumer Panel: -30°C +70°C (Op	perating) / -40°C +80°C (Storage)		
invironmental			Consumer Panel: -30°C +70°C (Opustrial Panel (Opt.): -25°C +75°C (
nvironmental	Temperature (Consumer)			Operating) / -45°C +85°C (Storage		
nvironmental	Temperature (Consumer) Temperature (Industrial)		ustrial Panel (Opt.): -25°C +75°C (Operating) / -45°C +85°C (Storage		
	Temperature (Consumer) Temperature (Industrial)	Indi	ustrial Panel (Opt.): -25°C +75°C (Operating) / -45°C +85°C (Storage)) / +5 +95% (Storage)	ge)	
nvironmental Accessory	Temperature (Consumer) Temperature (Industrial) Humidity	Indi	ustrial Panel (Opt.): -25°C +75°C (0 +10% +80% (Operating	Operating) / -45°C +85°C (Storage)) / +5 +95% (Storage)	ge)	
	Temperature (Consumer) Temperature (Industrial) Humidity Included	Indi	ustrial Panel (Opt.): -25°C +75°C (0 +10% +80% (Operating	Operating) / -45°C +85°C (Storage)) / +5 +95% (Storage)	ge)	
	Temperature (Consumer) Temperature (Industrial) Humidity Included	Indi	ustrial Panel (Opt.): -25°C +75°C (0 +10% +80% (Operating	Operating) / -45°C +85°C (Storage)) / +5 +95% (Storage)	ge)	
Accessory Type	Temperature (Consumer) Temperature (Industrial) Humidity Included Others	Indi Remote	ustrial Panel (Opt.): -25°C +75°C (0 +10% +80% (Operating	Operating) / -45°C +85°C (Storage) / +5 +95% (Storage) i Antenna, Stand Base, Air Conc	ge) iitionar	
Accessory Type	Temperature (Consumer) Temperature (Industrial) Humidity Included Others Net Weight (Kg)	Remote	ustrial Panel (Opt.): -25°C +75°C (C +10% +80% (Operating c Control, Key, Power Cable, Wi-F	Operating) / -45°C +85°C (Storage) / +5 +95% (Storage) i Antenna, Stand Base, Air Conc 177 Kg (1Pcs)	ge) litionar 192 Kg (1Pcs)	
Accessory	Temperature (Consumer) Temperature (Industrial) Humidity Included Others Net Weight (Kg) Gross Weight (Kg)	106 Kg (1Pcs) 138 Kg (1Pcs)	ustrial Panel (Opt.): -25°C +75°C (C +10% +80% (Operating e Control, Key, Power Cable, Wi-F 125 Kg (1Pcs)	Operating) / -45°C +85°C (Storage)) / +5 +95% (Storage) i Antenna, Stand Base, Air Conc 177 Kg (1Pcs) 213 Kg (1Pcs)	192 Kg (1Pcs) 234 Kg (1Pcs)	
Accessory Type	Temperature (Consumer) Temperature (Industrial) Humidity Included Others Net Weight (Kg) Gross Weight (Kg) Net Item Size (L x W x H mm)	106 Kg (1Pcs) 138 Kg (1Pcs) 830x256x1950 mm	ustrial Panel (Opt.); -25°C +75°C (C +10% +80% (Operating e Control, Key, Power Cable, Wi-F 125 Kg (1Pcs) 153 Kg (1Pcs) 980x256x2200 mm	Operating) / -45°C +85°C (Storage) j / +5 +95% (Storage) i Antenna, Stand Base, Air Conc 177 Kg (1Pcs) 213 Kg (1Pcs) 1105x256x2300 mm	192 Kg (1Pcs) 234 Kg (1Pcs) 1230x300x2500 mm	
Accessory	Temperature (Consumer) Temperature (Industrial) Humidity Included Others Net Weight (Kg) Gross Weight (Kg) Net Item Size (L x W x H mm)	106 Kg (1Pcs) 138 Kg (1Pcs) 830x256x1950 mm 2140x530x1120 mm	ustrial Panel (Opt.); -25°C +75°C (C +10% +80% (Operating e Control, Key, Power Cable, Wi-F 125 Kg (1Pcs) 153 Kg (1Pcs) 980x256x2200 mm	Operating) / -45°C +85°C (Storage) j / +5 +95% (Storage) i Antenna, Stand Base, Air Conc 177 Kg (1Pcs) 213 Kg (1Pcs) 1105x256x2300 mm 2440x530x1300 mm	192 Kg (1Pcs) 234 Kg (1Pcs) 1230x300x2500 mm 2520x530x1345 mm	

















Display & Digital Signage Solutions

World Trade Display reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. WTD, World Trade Display it's a registered trademarks of World Trade Display Srl. All rights reserved.