



- NOTE :
1. ALL DIMENSIONS ARE IN MILLIMETERS.
 2. TRANSUDCERS ARE LOCATED AT THE POSITIONS SHOWN, GLASS IS BEVELED UNDER THE TRANSUDCERS.
 3. CABLE ROUTING ADDS A MAXIMUM OF 4.0mm TO INDICATED SECTION OF SCREEN.
 4. 8X19 HOUSING MATES WITH CONTROLLER.
 5. REFLECTIVE ARRAY AND 2 TRANSUDCER ON THE FRONT OF THE GLASS.
 6. CABLE CLIP, MATERIAL: METAL.
 7. GLASS BOARD.
 8. CABLE, OUTER LAYER MATERIAL: PVCB601.
 9. THE TOUCH ACTIVE AREA IS LESS THAN THE VIEWABLE AREA TO FACILITATE SEALING.
 10. IT SHALL BE AVOIDED FOR 2 TO UNDERGO COMPRESSION,IMPACT, CRASH AND BREAK UP.

External Dimensions	362x239x4
Display Area	342x276
Active Area	340x272
Glass Thickness	4
Anti-Glare	Y <input type="checkbox"/> N <input checked="" type="checkbox"/>
DustPro	Y <input type="checkbox"/> N <input checked="" type="checkbox"/>
WaterPro	Y <input type="checkbox"/> N <input checked="" type="checkbox"/>
Anti-Vandal	Y <input type="checkbox"/> N <input checked="" type="checkbox"/>

CONNECTION CHART		INSULATION COLOR OVERALL SHIELD
PIN	SIGNAL	
1	GND KEY	
2	KEY	BLUE
3	Y-in2	BLUE
4	Y-out	BLUE
5	Y-in1	BLACK
6	GND	YELLOW
7	GND	
8	GND	GREEN
9	X-in2	WHITE
10	X-out	RED
11	X-in1	RED
12	KEY	