



NOTES:

NOTE:

1. ALL DIMENSIONS ARE IN MILLIMETERS.
THE UNSPECIFIED DIMENSION TOLERANCES ARE PLUS/MINUS 0.5.
ACTIVE AREA DIMENSIONS: (413(L) × 234(W))
VIEWABLE AREA DIMENSIONS: (415(L) × 234(W))
PROFILE DIMENSIONS: (463.5(L) × 284.5(W) × 6.4(D)).
2. SPECIFICATION.

- ① DUST-PROOF FRAME MATERIAL: ALUMINUM.
- ② 88X19 HOUSING MATES WITH CONTROLLER HOUSING MATERIAL: (98TU, 94V, 4Q8, ACX)
- ③ HOUSING OUTER LAYER MATERIAL: PVC60/RUBBER.
- ④ CABLE OUTER LAYER MATERIAL: PVC60/1.
- ⑤ GROUND LINE.
- ⑥ GLASS BOARD THICKNESS: 4

CONNECTION CHART		INSULATION COLOR OVERALL SHEILD
PIN	SIGNAL	
1	GND	
2	KEY	BLUE
3	Y-in2	BLUE
4	Vout	BLACK
5	Y-in1	YELLOW
6	GND	
7	GND	
8	GND	GREEN
9	X-in2	WHITE
10	X-out	RED
11	X-in1	RED
12	KEY	