



- NOTES:
1. ALL DIMENSIONS ARE IN MILLIMETERS.
  2. TRANSDUCERS ARE LOCATED AT THE POSITIONS SHOWN. GLASS IS BEVELED UNDER THE TRANSDUCERS.
  3. CABLE ROUTING ADDS A MAXIMUM OF 4.0mm TO INDICATED SECTION OF SCREEN.
  4. 8X19 HOUSING MATES WITH CONTROLLER.
  5. REFLECTIVE ARRAY AND 2 TRANSDUCER ON THE FRONT OF THE GLASS.
  6. CABLE CLIP, MATERIAL: METAL.
  7. GLASS BOARD.
  8. CABLE, OUTER LAYER MATERIAL: PVC8G01.
  9. THE TOUCH ACTIVE AREA IS LESS THAN THE VIEWABLE AREA TO FACILITATE SEALING.
  10. IT SHALL BE AVOIDED FOR 2 TO UNDERGO COMPRESSION, IMPACT, CRASH AND BREAK UP.
  11. BLACK TAPES ARE APPLIED ON THE BACK SURFACE OF THE GLASS OPPOSITE THE ARRAY PATTERNS.

External Dimensions	760x450x4
Display Area	716x406
Active Area	710x400
Glass Thickness	4
Anti-Glare	<input type="checkbox"/> Y <input checked="" type="checkbox"/> N
DustPro	<input type="checkbox"/> Y <input checked="" type="checkbox"/> N
WaterPro	<input type="checkbox"/> Y <input checked="" type="checkbox"/> N
Anti-Vandal	<input type="checkbox"/> Y <input checked="" type="checkbox"/> N

CONNECTION CHART		INSULATION COLOR OVERALL SHIELD
PIN	SIGNAL	
1	GND	
2	KEY	BLUE
3	Y-in2	BLUE
4	Yout	BLUE
5	Y-in1	BLACK
6	GND	YELLOW
7	GND	
8	GND	GREEN
9	X-in2	WHITE
10	Xout	RED
11	X-in1	RED
12	KEY	