



- NOTE 1:**
- ALL DIMENSIONS ARE IN MILLIMETERS.
 - TRANSUCERS ARE LOCATED AT THE POSITIONS SHOWN, THE HEIGHT OF TRANSUCERS ABOVE GLASS TO BE 3MM MAX.
 - CABLE ROUTING ADDS A MAXIMUM OF 4.0mm TO INDICATED SECTION OF SCREEN.
 - 8X19 HOUSING MATTER WITH CONTROLLER.
 - REFLECTIONAL ARRAY AND ② TRANSUCER ON THE FRONT OF THE GLASS.
 - CABLE CLIP, MATERIAL: METAL.
 - GLASS BOARD.
 - CABLE, OUTER LAYER MATERIAL: PVCBG01.
 - THE TOUCH ACTIVE AREA IS LESS THAN THE VIEWABLE AREA TO FACILITATE SEALING.
 - BLACK TAPES ARE APPLIED ON THE BACK SURFACE OF THE GLASS OPPOSITE THE ARRAY PATTERNS.
 - IT SHALL BE AVOIDED FOR ② TO UNDERGO COMPRESSION, IMPACT, CRASH AND BREAK UP.

External Dimensions	985x585x7
Display Area	944x544
Active Area	933x530
Glass Thickness	4
Anti-Glare	Y <input type="checkbox"/> N <input checked="" type="checkbox"/>
DustPro	Y <input type="checkbox"/> N <input checked="" type="checkbox"/>
WaterPro	Y <input type="checkbox"/> N <input checked="" type="checkbox"/>
Anti-Vandal	Y <input type="checkbox"/> N <input checked="" type="checkbox"/>

CONNECTION CHART		
PIN	SIGNAL	INSULATION COLOR OVERALL SHIELD
1	GND	
2	KEY	
3	Y-in2	BLUE
4	Y-out	BLUE
5	Y-in1	BLACK
6	GND	YELLOW
7	GND	
8	GND	GREEN
9	X-in2	WHITE
10	X-out	RED
11	X-in1	RED
12	KEY	